Subject Index

A

Acrylonitrile-butadiene-styrene, filled with glass beads and glass fibers, viscosity and die swell of, 1

B

Biaxial loading, failure of composite laminae under, 285
Bismaleimide polymers, advanced composites, processing and characterization, 367

C

Calcium carbonate, ultrafine, polypropylene filled with, fracture properties, 39
Capillaries, highly filled suspensions in, mat formation and unstable flows of, 242
Caprolactam, sorbed, effects on polyetheretherketone and poly(phenylene sulfide), 92
Carbon epoxy, Narmco 5208, room temperature aging of, 150
Carbon fibers
high-modulus surface-treated, interfacial adhesion, 122
properties of, modified by plasma polymerization, 109
Cellulose fibers, effects, polypropylene composites, 103
Chopped fiber composite material, creep rupture response, accelerated characterization of, 249
Coatings, glass fiber reinforcements, 44
Composite laminae, failure under biaxial loading, 285
Composite materials
see also specific type of composite
fiber-reinforced, inner-layer, interfacial strength determination, 199
micromechanical characterization of, 140
three-dimensional stress analysis, using isodyne techniques, 270
Crack Rail Shear specimen, mode III intralaminal toughness, 293
Creep rupture, chopped fiber composite, accelerated characterization of, 249
Crystallization kinetics, thermal history of melt effects, 361

D

Delamination shape, aramid-epoxy-aluminum laminates, with fatigue cracks, 322
Dielectric constant, epoxy resins filled with, properties of, 205
Double Cantilever Beam specimen, fracture toughness property, composite laminates, 305

E

Elastomeric matrix, short fibers, adhesion, 256
Electromagnetic interference (EMI)-shielding, synergism on, metal- and ferroelectric-particle filled polymers, 52
Electron microscopy, scanning, polymer blend, glass fiber composite, 222
Epoxies
DGEBA
low temperature relaxation of, 173
study of interfaces using single-fiber-composite test, 385
dielectric-filled, properties of, 205
glass fiber-, composite interfaces, 424
graphite fibers in, interfacial shear strength studies, 226
Extruders, twin screw, processing of fiber reinforced thermoplastics, 98

F

Fatigue cracks
aramid-epoxy-aluminum laminates with, delamination shape effects, 322
propagation, mica-filled polyolefins, 62
Ferroelectric particles, polymers filled with, synergism on EMI-shielding, 52
Fiber mats, prelocated, molds with, liquid flow in, 414
Fillers
particles, dispersion of, 215
surface of composites, expression of activity of, 194
Fluorescence, X-ray, polymer blend, glass fiber composite, 222

G

Gas chromatography, inverse, filler surface of composites, 194
Glass beads, acrylonitrile-butadiene-styrene filled with, viscosity and die swell of, 1
Glass fibers
acrylonitrile-butadiene-styrene filled with, viscosity and die swell of, 1
epoxy, composite interfaces, 424
high-performance, study of interfaces using single-fiber-composite test, 385
Noryl reinforced with
rheological properties and fiber orientation, 84
rheological properties of, 78
polymer blend, scanning electron microscopy and X-ray fluorescence analysis, 222
polypropylene reinforced with, 8, 16
reinforcements, analysis of coatings on, 44
Glass flake, polypropylene reinforced with, injection molding of, 352
Graphite-epoxy composites, interfacial shear strength, failure modes and, 162
Graphite fibers
epoxy, interfacial shear strength studies, 226
properties of, modified by plasma polymerization, 109
Graphite/polyimide composites, improved toughness, 134

H

Hybrid sandwich specimen, under distributed load, interlaminar shear test by, 463

I

Injection molding
glass flake reinforced polypropylene, flake orientation and stiffness, 352
long-fiber thermoplastic composites, tensile properties of, 313
short fibers, processing variables on microstructure of, 345
Interfacial adhesion, high-modulus surface-treated carbon fibers, ionic copolymers and, 122
Interlaminar stresses, parameters affecting, tapered laminates, 374
Intralaminal fracture toughness, mode III, composite materials, 293
Ionic copolymers, high-modulus surface-treated carbon fibers and, interfacial adhesion, 122
Isodyne techniques, three-dimensional stress analysis, composite structures, 270

L

Laminates
aramid-epoxy-aluminum
time-dependent response, 328
with fatigue cracks, delamination shape effects, 322
composite, fracture toughness property, Double Cantilever Beam specimen, 305
tapered, parameters affecting interlaminar stresses, 374

M

Mat formation, unstable flows and, capillaries and continuous processors, 242
Metal, polymers filled with, synergism on EMI-shielding, 52
Molds, prelocated fiber mats, liquid flow in, 414

N

Narmco 5208 carbon-epoxy, room temperature aging of, 150

Subject Index

A

Acrylonitrile-butadiene-styrene, filled with glass beads and glass fibers, viscosity and die swell of, 1

B

Biaxial loading, failure of composite laminae under, 285
Bismaleimide polymers, advanced composites, processing and characterization, 367

C

Calcium carbonate, ultrafine, polypropylene filled with, fracture properties, 39
Capillaries, highly filled suspensions in, mat formation and unstable flows of, 242
Caprolactam, sorbed, effects on polyetheretherketone and poly(phenylene sulfide), 92
Carbon epoxy, Narmco 5208, room temperature aging of, 150
Carbon fibers
high-modulus surface-treated, interfacial adhesion, 122
properties of, modified by plasma polymerization, 109
Cellulose fibers, effects, polypropylene composites, 103
Chopped fiber composite material, creep rupture response, accelerated characterization of, 249
Coatings, glass fiber reinforcements, 44
Composite laminae, failure under biaxial loading, 285
Composite materials
see also specific type of composite
fiber-reinforced, inner-layer, interfacial strength determination, 199
micromechanical characterization of, 140
three-dimensional stress analysis, using isodyne techniques, 270
Crack Rail Shear specimen, mode III intralaminal toughness, 293
Creep rupture, chopped fiber composite, accelerated characterization of, 249
Crystallization kinetics, thermal history of melt effects, 361

D

Delamination shape, aramid-epoxy-aluminum laminates, with fatigue cracks, 322
Dielectric constant, epoxy resins filled with, properties of, 205
Double Cantilever Beam specimen, fracture toughness property, composite laminates, 305

E

Elastomeric matrix, short fibers, adhesion, 256
Electromagnetic interference (EMI)-shielding, synergism on, metal- and ferroelectric-particle filled polymers, 52
Electron microscopy, scanning, polymer blend, glass fiber composite, 222
Epoxies
DGEBA
low temperature relaxation of, 173
study of interfaces using single-fiber-composite test, 385
dielectric-filled, properties of, 205
glass fiber-, composite interfaces, 424
graphite fibers in, interfacial shear strength studies, 226
Extruders, twin screw, processing of fiber reinforced thermoplastics, 98

F

Fatigue cracks
aramid-epoxy-aluminum laminates with, delamination shape effects, 322
propagation, mica-filled polyolefins, 62
Ferroelectric particles, polymers filled with, synergism on EMI-shielding, 52
Fiber mats, prelocated, molds with, liquid flow in, 414
Fillers
particles, dispersion of, 215
surface of composites, expression of activity of, 194
Fluorescence, X-ray, polymer blend, glass fiber composite, 222

G

Gas chromatography, inverse, filler surface of composites, 194
Glass beads, acrylonitrile-butadiene-styrene filled with, viscosity and die swell of, 1
Glass fibers
acrylonitrile-butadiene-styrene filled with, viscosity and die swell of, 1
epoxy, composite interfaces, 424
high-performance, study of interfaces using single-fiber-composite test, 385
Noryl reinforced with
rheological properties and fiber orientation, 84
rheological properties of, 78
polymer blend, scanning electron microscopy and X-ray fluorescence analysis, 222
polypropylene reinforced with, 8, 16
reinforcements, analysis of coatings on, 44
Glass flake, polypropylene reinforced with, injection molding of, 352
Graphite-epoxy composites, interfacial shear strength, failure modes and, 162
Graphite fibers
epoxy, interfacial shear strength studies, 226
properties of, modified by plasma polymerization, 109
Graphite/polyimide composites, improved toughness, 134

H

Hybrid sandwich specimen, under distributed load, interlaminar shear test by, 463

I

Injection molding
glass flake reinforced polypropylene, flake orientation and stiffness, 352
long-fiber thermoplastic composites, tensile properties of, 313
short fibers, processing variables on microstructure of, 345
Interfacial adhesion, high-modulus surface-treated carbon fibers, ionic copolymers and, 122
Interlaminar stresses, parameters affecting, tapered laminates, 374
Intralaminal fracture toughness, mode III, composite materials, 293
Ionic copolymers, high-modulus surface-treated carbon fibers and, interfacial adhesion, 122
Isodyne techniques, three-dimensional stress analysis, composite structures, 270

L

Laminates
aramid-epoxy-aluminum
time-dependent response, 328
with fatigue cracks, delamination shape effects, 322
composite, fracture toughness property, Double Cantilever Beam specimen, 305
tapered, parameters affecting interlaminar stresses, 374

M

Mat formation, unstable flows and, capillaries and continuous processors, 242
Metal, polymers filled with, synergism on EMI-shielding, 52
Molds, prelocated fiber mats, liquid flow in, 414

N

Narmco 5208 carbon-epoxy, room temperature aging of, 150

Noryl
glass fiber reinforced
rheological properties and fiber orientation, 84
rheological properties of, 78

P

Plasma polymerization, modification, carbon/graphite fibers, 109
Poly(aryl-ether-ether-ketone), crystallization of, 361
Polyetheretherketone, sorbed caprolactam effects, 92
Polyethylene
dispersion of filler particles, 215
low density blend matrices, poypropylene and, short glass fibers based composites, 117
Polymer blends
bulk modulus, thermal expansivity and, 407
metal- and ferroelectric-particle filled, synergism on EMI-shielding, 52
organic, wood cellulose as reinforcement in, 69
scanning electron microscopy, X-ray fluorescence analysis and, 222
Polyolefins, mica-filled, fatigue crack propagation, 62
Poly(phenylene sulfide), sorbed caprolactam effects, 92
Poly-p-phenylene terephthalamide/nylon, molecular and particulate composites, rheological and mechanical characteristics, 429
Polypropylene
composites, cellulose fibers in, 103
filled with ultrafine calcium carbonate, fracture properties and strength, 39
glass-fiber-reinforced, 8, 16
glass flake reinforced, injection molding of, 352
injection molded short fiber reinforced, processing variables on microstructure of, 345
low density polyethylene blend matrices, short glass fibers based composites, 117
Poly(styryl pyridine), composite materials based on, micromechanical characterization of, 140

S

Shear strength
interfacial studies, single-filament-composite test, 226, 389
interlaminar test, hybrid sandwich specimen under distributed load, 463
Short fibers
distribution, simulating in thin sheets, 57
elastomeric matrix-, adhesion, 256
glass fiber reinforced Noryl
rheological properties and fiber orientation, 84
rheological properties of, 78
injection molded, processing variables on microstructure of, 345
polypropylene/low density polyethylene blend matrices, 117
reinforced melts, prediction of flow and orientation behavior, 337
thermoplastics reinforced with
fiber length effects, 454
structure-properties relations, 28
void formation, 449
Single-fiber-composite test, study of interfaces, high-performance glass fibers and DGEBA epoxies, 385
Single-filament-composite test, interfacial shear strength studies using, 226, 389
Slurry deposition, long-fiber reinforced thermoplastic matrix composites, 145
Structure-properties relations, short fiber-reinforced thermoplastics, 28

T

Thermal expansivity, bulk modulus and, polymer composites, 407
Thermoplastics
fiber reinforced, processing with corotating twin srew extruders, 98
injection molded long-fiber composites, tensile properties of, 313
matrix composites
long-fiber reinforced by slurry deposition, 145
stamping of, 261
short-fiber reinforced
fiber length effects, 454
structure-properties relations, 28
void formation, 449
Thermoset cure behavior, characterization, differential scanning calorimetry, 439
Thermosetting composite materials, transfer-molded, weld line studies, 184

V

Void, formation, short-fiber thermoplastic composites, 449

W

Weld line studies, transfer-molded thermosetting composite materials, 184
Wood cellulose, reinforcement, organic polymer composites, 69

Author Index

Allard, R. C., 62
Arroyo, M., 117
Avalos, F., 117

Bataille, P., 103
Becht, G. J., 293
Belfiore, L. A., 122
Bell, J. P., 162
Benkirane, A., 57
Bigg, D. M., 145, 261
Boluk, M. Y., 215
Bouti, A., 352

Camberlin, Y., 367
Caux, X., 140
Chalifoux, J.-P., 57, 62
Chamorro, C., 256
Charrier, J.-M., 28
Chen, J. J., 205, 470
Cheng, C., 122
Chouliotis, A., 150
Cigánek, M., 194
Cole, K. C., 150
Coulon, G., 140

Dagli, G., 109
Dainty, R. V., 305
Daoust, J., 374
Davé, R., 199
Day, M., 360
Delvigs, P., 134
Denault, J., 313
Deslandes, Y., 360
Deteresa, S. J., 202
Doshi, S. R., 28
Dressler, M., 194
Drumm, C. A., 44

Eduljee, R. F., 184
Escaig, B., 140

Fisa, B., 352
Foster, B., 313

Gaudert, P. C., 305
Geil, P. H., 173
Gillespie, J. W., Jr., 184, 293
Giraud, Y., 367
Gogos, C. G., 242
Gupta, V. B., 8, 16

Hechler, J.-J., 150
Henstenburg, R. B., 226, 389
Hiscock, D. F., 145
Hoa, S. V., 374
Huang, Y. H., 205, 470

Ibarra, L., 256

Jang, B. Z., 205, 470

Kalyon, D. M., 242
Kamal, M. R., 337, 344
Kenig, S., 78, 84, 449, 454
Krieger, W., 52, 203
Kruse, K.-D., 52, 203
Kyo, T., 429

Labossière, P., 285
Lam, P. W. K., 439
Lazzeri, A., 39
Lee, L. J., 414
Lee, S., 305
Levita, G., 39
Liao, Y.-T., 424
Lopez, P., 367
Lorenzo, L., 199

Macheret, J., 322
Macheret, Y., 328
Marchetti, A., 39
Marom, G., 463
Maurer, F. H. J., 409
Meissonnier, J., 367
Mennig, G., 8, 16
Michell, A. J., 69
Mittal, R. K., 8, 16
Molnar, J. A., 414
Morris, D. H., 249
Mutel, A. T., 337

Narkis, M., 78, 84, 449, 454
Neale, K. W., 285
Netravali, A. N., 226, 385
Nicolais, L., 202
Noël, D., 150

Overbury, K. C., 150

Pangrle, S., 173
Papazoglou, E., 409
Park, H.-S., 429
Petermann, J., 52, 203
Phoenix, S. L., 226, 385, 389
Pindera, J. T., 270
Pindera, M.-J., 328
Preston, J. R., 261

Ricard, L., 103
Roche, F., 57
Rosensaft, M., 463

Sabir, N.-F., 360
Saini, D. R., 222
Sanschagrin, B., 57
Sapieha, S., 103
Schreiber, H. P., 215
Schultz, J. M., 222
Schwartz, P., 226, 385
Scott, R. F., 305
Shah, R. J., 122
Sharma, P. K., 8, 16
Siegman, A., 449, 454
Siegmann, A., 78, 84
Simha, R., 409
Singh, P., 344
Sung, N.-H., 109
Suprunchuk, T., 360

Teply, J. L., 322
Ter Haseborg, J.-L., 52, 203
Trevino, L., 414

Ulicny, J. C., 44
Utracki, L. A., 269

Vaxman, A., 78, 84, 449, 454
Viot, J.-F., 367
Vu-Khanh, T., 62, 269, 313, 352

Wall, D., 98
Wenderoth, K., 52, 203
Wilfong, D. L., 92
Williams, T. O., 328
Wimolkiatisak, A. S., 162
Winter, E. F. M., 322
Wolters, J., 8, 16
Wu, C. S., 173

Yen, S.-C., 249
Yilmazer, U., 1, 242

Zadorecki, P., 69
Zee, R. H., 205, 470